

Samar

cat. A

100% polyester FR
Flame retardant - 50.000 Martindale




7052.04




7052.24




7052.25




7052.14




7052.13




7052.27




7052.17




7052.16



7052.36




7052.35



7052.37



7052.40



7052.39



7052.38




7052.31



7052.47



7052.42




7052.50




7052.49



7052.41



7052.01



7052.46



7052.02




7052.05




7052.43



7052.44



7052.51




7052.48




7052.08



7052.10



7052.21




7052.07




7052.18




7052.09




7052.12



7052.11




7052.34




7052.19




7052.22




7052.23



7052.29



7052.26



7052.30



7052.33

laCividdina

cat. A

2023

Samar

eco-sustainable

Technical details

Composition	100% polyester FR
Weight	Gr./ml. 663
Abrasion test	Martindale - ISO 12947-2: 50.000 rubs
Lightfastness	ISO 105-B02: 6
Pilling	ISO 12945-2: 4/5
Fastness to rubbing	ISO 105-X12: Wet 4/5 Dry 4/5
Flame retardant	EN 1021/1-2 BS 5852, crib 5 NF P 92/503-507, M1 DIN 4102, B1 IMO 2010 FTP part 8 UNI 9175, classe 1 Cal TB 117 NFPA 260, class 1
Environment	CERTIFIED TO OEKO-TEX® STANDARD 100