

Stretchy

cat. B


100% PES FR  
Flame retardant - 100.000 Martindale



1



24



12



28



18



23



7



27



30



13



32



48



42




45



6



47



11



5



2



29



34



35



3



9




8



31



33



36



14



19



25



26




37



38



39



15



4



44



43



41




16



20



40



17




10



21



46



22



|  |                     |  |                   |  |
|--|---------------------|--|-------------------|--|
| <div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> </div> | Stretchy            |  | Technical details |  |
|  | Composition         | 100% PES FR  |                   |  |
|  | Weight              | Gr./m² 300   |                   |  |
|  | Abrasion test       | Martindale - ISO 12947-2 100.000 rubs  |                   |  |
|  | Lightfastness       | ISO 105-B02: 5   |                   |  |
|  | Pilling             | ISO 12945-2: 5   |                   |  |
|  | Fastness to rubbing | ISO 105-X12: Wet 4/5<br>Dry 4/5  |                   |  |
|  | Flame retardant     | UNI 9175 classe 1IM<br>EN 1021-1<br>EN 1021-2<br>BS 5852-1 cigarette test<br>BS 5852-1 match test<br>BS 5852 crib 5<br>TB 117 2013 |                   |  |
|  | Feature             | STRETCH MATERIAL   |                   |  |
|  |                     |  |                   |  |
| laCividina   |                     | cat. B   | 2023              |  |